



Description

AC Products' TPC Stripper may be used to help remove temporary protective coatings that have been applied incorrectly or are otherwise no longer peelable. TPC Stripper is a strong solution and should be used with care. This stripper is not to be used for general coating removal. When properly applied, the coatings are hand strippable. **Carefully read the following instructions before use.**

Product Precautions

WARNING! CONTAINS DIBASIC ESTER. KEEP OUT OF REACH OF CHILDREN. Keep away from sparks, hot glowing surfaces, and open flame. Use with adequate ventilation. When necessary, use a Niosh approved respirator. Do not take internally. Avoid prolonged contact with skin. Keep container closed when not in use. Consult Material Safety Data Sheet before use.

Storage

Store at temperatures above 50°F. and below 110°F.

Product Use Instructions

Read these instructions thoroughly before use.

1. In an inconspicuous area, apply a small amount of the TPC Stripper to the base material and check for incompatibility before general use. Test on base material for one hour, then remove and check appearance of the base material. If the TPC Stripper attacks the base material, do not use! **This stripper will attack acrylic surfaces.**
2. Plug drains before application of the stripper. If stripper accidentally enters drain flush immediately with large volume of water as stripper may attack plastic plumbing.
3. Cover and protect all adjacent areas that may be splashed. This product is a stripper. Be careful to protect painted, lacquered, or glossy surfaces that may come in contact with stripper.
4. Apply TPC Stripper liberally to the coated areas only using a soft bristle brush. **DO NOT EXPOSE BARE SURFACES TO STRIPPER.**
5. Allow to stand for 15-20 minutes. Covering the stripper with plastic wrap or other non porous covering will retard evaporation of the active ingredient and improve stripper performance. The coating will swell and wrinkle as the stripper is working. Do not allow to stand longer than 60 minutes unless testing shows prolonged exposure to be safe.
6. When the stripper has loosened the film, attempt to peel or use a non-scratch pad to safely remove.
7. After all the loosened film has been removed, thoroughly wash the surface with soapy water.

Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product, which is proved to be defective. Any claim of defective product must be received in writing within one (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss, or damage resulting from use of this product.

AC Products, Inc.
172 East La Jolla Street, Placentia, CA 92870
Ph: 714.630.7311 / Fax: 714.666.8309
E-Mail: acpaerosp@quakerchem.com Web Site: www.epmar.com

A Subsidiary of Quaker Chemical Corporation